

## SPECIAL NOTE FOR RIGHT-OF-WAY MONUMENTS

This Special Note will apply when indicated on the plans or in the proposal.

**1.0 DESCRIPTION.** Furnish and install right-of-way monuments at the location and with the type shown on the plans.

**2.0 MATERIALS.** Furnish Aluminum Alloy monuments specified on the Standard Drawing.

**3.0 CONSTRUCTION.** Install right-of-way monuments at the earliest opportunity on a project as determined by the project manager. Install right-of-way monuments under the direct supervision of a Kentucky Licensed Professional Land Surveyor.

Establish right-of-way monuments from existing Primary or Supplemental control monuments with an accuracy of 1:15,000 or greater.

Place right-of-way monument information on a Control Monument Information Sheet (Exhibit 300-04 of the Highway Design Manual) provided by the Department. Place the completed Control Monument Information Sheet in a final survey report. Completely fill out the Control Monument Information Sheet, including the signature and registration number of the Kentucky Licensed Professional Land Surveyor in charge of the monumentation. Submit the Final Survey Report to the KYTC Survey Coordinator in the Division of Highway Design and the Engineer.

Reset all monuments disturbed or destroyed during or prior to construction, with the same accuracy as stated previously. Update the Control Monument Information Sheet with any new data and include in the Final Survey Report. Ensure the Kentucky Licensed Professional Land Surveyor in charge of the re-monumentation signs and places his registration number on the updated Control Monument Information Sheet. Submit the updated Final Survey Report to the KYTC Survey Coordinator in the Division of Highway Design, the Engineer, and the Kentucky Licensed Professional Land Surveyor who set the original monuments.

Right-of-way monuments that cannot be established at the planned location due to inaccessibility should be witnessed by a witness right-of-way monument on both lines and labeled as such (see Standard Drawing).

Use a 6-foot long orange witness post to aid in locating right-of-way monuments. Set the witness post within the public right-of-way and within one foot of the monument location. Label the witness post to denote that the point is KYTC right-of-way (See Standard Drawing).

**4.0 MEASUREMENT AND PAYMENT.** The Department will measure the quantity by each individual unit.

**5.0 PAYMENT.** The Department will make payment for the completed and accepted quantities under the following:

<u>Code</u>	<u>Pay Item</u>	<u>Pay Unit</u>
2429	Right-of-Way Monument, Type 1	Each
2430	Right-of-Way Monument, Type 1A	Each
2431	Witness R/W Monument Type 2	Each
2432	Witness Post	Each